

HEAVY DUTY / HEAVY DUTY+ GREASE

High Load

Premium quality extreme pressure grease, highly versatile, designed for intensive applications in heavy industries: steel, construction, transport, etc.

Applications

- Conveyors,
- Lifting equipment,
- Truck wheel hubs,
- Medium-power electric motors,
- Water pumps,
- Fans, etc.



PROPERTIES

Very good oxidation stability for continuous use up to 130°C continuously



ADVANTAGES

No premature ageing of the grease up to 130°C in continuous use

Contains extreme pressure additives

EP

Excellent performance under heavy

Good behaviour in the presence of



Very good resistance to washing out, which limits grease loss and therefore reduces consumption

Contains anti-wear additives

AW

Excellent protection against wear

Characteristics	Method	Unit	HEAVY DUTY	HEAVY DUTY +
Operating temperature		°C	-30°C to + 130°C	-30°C to + 150°C
Colour			Blonde to dark blonde	Fluorescent green
Texture			Smooth	Smooth
Density	NF-T-60 101	g/cm ³	0,94	0,89
Worked penetration 60 strokes	ISO 2137	10 ⁻¹ mm	265/295	265/295
NLGI grade	ISO 20623		2	2
4 EP balls welding	ISO 20623	Kg	315	315
Type of thickener			Lithium/calcium with EP additives	Lithium with EP additives
Nature of base oil			Mineral	Mineral
Viscosity of base oil at 40°C	ASTM D 445	cSt	150	150
Viscosity of base oil at 100°C	ASTM D 445	cSt	11.8	15
Drop point	ISO 2176	°C	190	> 190

Available packaging

HEAVY DUTY



1kg

400g

5kg

15kg, 50kg and 190kg

HEAVY DUTY + single-point lubricators

READY 60cc and 125cc
DRIVE 60cc, 120cc,
250cc and 500cc
SMART 125cc

