

UNIVERSAL/UNIVERSAL+ GREASE

Multi-purpose

Multi-purpose grease based on anhydrous calcium (UNIVERSAL), offering a high-performance alternative to lithium with excellent value for money.

Applications

- Agricultural equipment
- Washing machines
- Handling equipment
- General mechanics
- Low-power electric motors
- Car wheel bearings,
- Small tools, etc.



PROPERTIES

ADVANTAGES

Excellent lubrication performance	€	Universal thus ensures very good protection for mechanisms with excellent value for money
Good oxidation stability up to 120°C		No premature ageing of the grease across the entire of temperature
Very good resistance to water and load		Lubrication remains optimal in a humid environment and under load, thus helping to increase your productivity
Very good pumpability		The product is easy to use

Feature	Method	Unit	UNIVERSAL	UNIVERSAL+
Operating temperature		°C	-20°C to 120°C	-30°C to +130°C
Colour			Blonde to dark blonde	Blonde to dark blonde
Texture			Smooth	Smooth
Density	NF-T-60 101	g/cm ³	0.94	0.94
Worked penetration 60 strokes	ISO 2137	10 ⁻¹ mm	265/295	265/295
NLGI grade	ISO 6743		2	2
Speed resistance		NDm*	600,000	500,000
Type of thickener			Anhydrous calcium	Calcium/lithium
Type of base oil			Mineral	Mineral
Viscosity of base oil at 40°C	ASTM D 445	cSt	125	150
Base oil viscosity at 100°C	ASTM D 445	cSt	13	11.5
Drop point	ISO 2176	°C	>140	190

* NDm is a speed factor where N is the rotational speed in rpm and Dm is the average bearing diameter (d+D)/2

AVAILABLE PACKAGING

UNIVERSAL



UNIVERSAL+

single-point lubricators

READY 60cc and 125cc
 DRIVE 60cc, 120cc,
 250cc and 500cc
 SMART 125cc

